



 <p>BRITISH GEOLOGICAL SURVEY LOCAR</p>	<p>BOREHOLE/PIEZOMETER COMPLETION INFORMATION</p>
---	--

LOCAR No.: PL11K Wellmaster No.: SU57/237 SOBI No.: SU57SW110

Location : FRILSHAM MEADOW
NGR : 4538 1739
OD Levels :
at top manhole cover
at top casing
other (specify)

Drilling Company : BDF
Driller : NIXON
Date Drilling Commenced : 13.8.02
Date Drilling Completed : 13.8.02
Date Borehole Completed : 14.8.02
BGS/WMC Supervisor : NEWMAN J

Borehole Construction Details		Construction Materials	
Bottom of borehole (as drilled)	6 m bgl	Casing material:	Surface casing steel
Borehole diameter	(10 1/4") 260 mm	Screen material:	
Depth of backfill (in base of borehole)	5.45 m bgl	Slot size:	1 mm
Bottom of piezometer*	5.30 m bgl	Screen/casing diameter:	mm
Bottom of screen*	5.30 m bgl	Backfill material:	
Top of screen*	5.0 m bgl	Filter pack material:	
Top of filter pack†	4.0 m bgl	Seal material:	
Top of seal†	3.0 m bgl	Grout material:	
Top of grout†	m bgl		
* Measurement based on total length of pipe.			
† Measured with a weighted tape measure			

Surface Completion *Surface casing (steel) with flange plate @ 0.65m agl.*

Type (circle one): ~~A (small)~~ ~~C~~ ~~D~~ ~~B~~ Height of top of manhole cover above ground level: m
Top of casing below top of manhole cover: m

Notes:

BOREHOLE CONSTRUCTION DIAGRAM ON REVERSE

BOREHOLE CONSTRUCTION DIAGRAM

